

Rubber profiles



OSE-P 14 36 00

Height	36 mm (1.42")
Foot	T Foot
Sealing lip	One
Width	14 mm (0.55")
Diameter sensor channel	Ø 11 mm (0.43")
Foot width	9.6 mm
Material	EPDM
Roll length	50 m (164 ft)
Compatible OSE sensors	OSE-S 65xx, 66xx, 67xx and 68xx
Compatible bumpers	OSE-B 3012, OSE-B 3512



OSE-P 14 36 04

Height	36 mm (1.42")
Foot	T Foot tear-off
Sealing lip	One
Width	14 mm (0.55")
Diameter sensor channel	Ø 11 mm (0.43")
Foot width	5 mm / 7.4 mm (tear-off foot)
Material	EPDM
Roll length	50 m (164 ft)
Compatible OSE sensors	OSE-S 65xx, 66xx, 67xx and 68xx
Compatible bumper	OSE-B 3512



OSE-P 20 40 00

Height	40 mm (1.57")
Foot	T Foot tear-off
Sealing lip	None
Width	20 mm (0.79")
Diameter sensor channel	Ø 10.9 mm (0.43")
Foot width	15.5 mm / 19.5 mm (tear-off foot)
Material	EPDM
Roll length	30 m (98.5 ft)
Compatible OSE sensor	OSE-S 1xxx
Compatible bumper	OSE-B 3518
Compatible retainer	ALU-2007



OSE-P 20 40 01

Height	40 mm (1.57")
Foot	T Foot
Sealing lip	One
Width	20 mm (0.79")
Diameter sensor channel	Ø 10.9 mm (0.43")
Foot width	15.3 mm
Material	EPDM
Roll length	40 m (131.2 ft)
Compatible OSE sensors	OSE-S 65xx, 66xx, 67xx and 68xx
Compatible bumper	OSE-B 3518
Compatible retainers	ALU-2007, ALU-2509



OSE-P 25 30 00

Height	30 mm (1.18")
Foot	T Foot tear-off
Sealing lip	None
Width	25 mm (0.98")
Diameter sensor channel	Ø 10.9 mm (0.43")
Foot width	15.8 mm / 20 mm (tear-off foot)
Material	EPDM
Finger detection	Yes
Dead surface region	80 mm (3.15")
Roll length	50 m (164 ft)
Compatible OSE sensor	OSE-S 1xxx
Compatible bumper	OSE-B 3518
Compatible retainer	ALU-2509



OSE-P 25 33 00

Height	33 mm (1.3")
Foot	C Foot
Sealing lip	None
Width	25 mm (0.98")
Outer diameter	Ø 13.4 mm (0.53")
Diameter sensor channel	Ø 10.9 mm (0.43")
Foot width	16 mm (0.63")
Material	EPDM
Finger detection	Yes
Dead surface region	50 mm (1.97")
Roll length	25 m (82 ft)
Compatible OSE sensor	OSE-S 1xxx
Compatible bumper	OSE-B 3518
Compatible retainer	ALU-2509

Rubber profiles



OSE-P 25 33 00 NBR

Height	33 mm (1.3")
Foot	C Foot
Sealing lip	None
Width	25 mm (0.98")
Outer diameter	Ø 13.4 mm (0.53")
Diameter sensor channel	Ø 10.9 mm (0.43")
Foot width	15.8 mm / 20 mm (tear-off foot)
Material	NBR
Finger detection	Yes
Dead surface region	50 mm (1.97")
Roll length	50 m (164 ft)
Compatible OSE sensors	OSE-S 1xxx
Compatible bumper	OSE-B 3518
Compatible retainer	ALU-2509



OSE-P 25 75 00

Height	75 mm (2.95")
Foot	T Foot
Sealing lip	One
Width	25 mm (0.98")
Diameter sensor channel	Ø 21 mm (0.83")
Foot width	15.8 mm / 20 mm (tear-off foot)
Material	EPDM
Roll length	30 m (98.5 ft)
Compatible OSE sensors	OSE-S 65xx, 66xx, 67xx and 68xx
Compatible pneumatic sensors	For all DW types
Compatible bumper	OSE-B 5518
Compatible retainer	ALU-2509



OSE-P 25 75 01

Height	75 mm (2.95")
Foot	T Foot
Sealing lip	One
Width	25 mm (0.98")
Diameter sensor channel	Ø 10.9 mm (0.43")
Foot width	15.5 mm / 19.5 mm (tear-off foot)
Material	EPDM
Roll length	30 m (98.5 ft)
Compatible OSE sensors	OSE-S 65xx, 66xx, 67xx and 68xx
Compatible bumper	OSE-B 5518
Compatible retainer	ALU-2509



OSE-P 25 90 00

Height	30 mm (1.18")
Foot	T Foot
Sealing lip	One
Width	25 mm (0.98")
Diameter sensor channel	Ø 10.9 mm (0.43")
Foot width	18.5 mm
Material	EPDM
Roll length	30 m (98.5 ft)
Compatible OSE sensors	OSE-S 65xx, 66xx, 67xx and 68xx
Compatible bumper	OSE-B 6728
Compatible retainer	ALU-2509



OSE-P 30 58 00

Height	58 mm (2.28")
Foot	Clips foot
Sealing lip	None
Width	30 mm (1.18")
Outer diameter	Ø 13.4 mm (0.53")
Diameter sensor channel	Ø 10.9 mm (0.43")
Foot width	17 mm (0.67")
Material	EPDM
Finger detection	Yes
Dead surface region	80 mm (3.15")
Roll length	50 m (164 ft)
Compatible OSE sensors	OSE-S 1xxx
Compatible bumper	OSE-B 5518
Compatible retainer	ALU-3009



OSE-P 30 65 00

Height	65 mm (2 9/16")
Foot	T Foot Tear-off
Sealing lip	One
Width	30 mm (1.18")
Diameter sensor channel	Ø 11 mm (0.43")
Foot width	15.5 mm / 19.5 mm (tear-off foot)
Material	EPDM
Roll length	30 m (98.5 ft)
Compatible OSE sensors	OSE-S 65xx, 66xx, 67xx and 68xx
Compatible bumper	OSE-B 5328
Compatible retainer	ALU-2509

Rubber profiles



OSE-P 30 90 01

Height	90 mm (3.54")
Foot	C Foot
Sealing lip	None
Width	30 mm (1.18")
Outer diameter	Ø 13.4 mm (0.53")
Diameter sensor channel	Ø 10.9 mm (0.43")
Foot width	18 mm (0.71")
Material	EPDM
Finger detection	Yes
Dead surface region	50 mm (1.97")
Roll length	25 m (82 ft)
Compatible OSE sensors	OSE-S 1xxx
Compatible bumper	OSE-B 5518
Compatible retainer	ALU-3009



OSE-P 40 40 00

Height	40 mm (1.57")
Foot	Double-T Foot
Sealing lip	None
Width	40 mm (1.57")
Diameter sensor channel	Ø 21 mm (0.83")
Material	EPDM
Roll length	15.2 m (50 ft)
Compatible OSE sensors	OSE-S 50xx



OSE-P 45 60 00

Height	60 mm (2.36")
Foot	T Foot
Sealing lip	Two
Width	45 mm (1.77")
Diameter sensor channel	Ø 10.9 mm (0.43")
Foot width	15.5 mm / 19.8 mm (tear-off foot)
Material	EPDM
Roll length	25 m (82 ft)
Compatible OSE sensors	OSE-S 65xx, 66xx, 67xx and 68xx
Compatible bumper	OSE-B 5328



OSE-P 45 60 04

Height	60 mm (2.36")
Foot	Torque-Force Foot
Sealing lip	One
Width	45 mm (1.77")
Diameter sensor channel	Ø 11 mm (0.43")
Foot width	33 mm (1.30")
Material	EPDM
Roll length	30 m (98.5 ft)
Compatible OSE sensors	OSE-S 65xx, 66xx, 67xx and 68xx
Compatible bumper	OSE-B 5328



DW PROFILE 21 Z 58

Height	25 mm (0.98")
Foot	C Foot
Sealing lip	None
Width	26 mm (1.02")
Diameter sensor channel	Ø 21 mm (0.83")
Foot width	20 mm (0.79")
Material	NBR
Roll length	25 m (82 ft)
Compatible pneumatic sensors	For all DW types
Compatible retainer	ALU-2509