

Industrial air / liquid



- Industrial demi element air / liquid housings
- Available in 5" with Demi Z style locator
- Range of closure options



Specifications

Materials of Construction Housing:	316L/1.4404
Surface Finish	Mechanical polishing
Internal Upstream:	BSP: Mechanical polishing to <0.8µm Ra
Internal Downstream:	Triclamp: Mechanical polishing to <0.4µm Ra
External:	Mechanical polishing
Cartridge Socket:	Z style
Number of Cartridges:	1
Technical Design Data	PED 2014/68/EU
Design Code:	SEP (Art 4.3)
PED Category:	1 or 2
PED Fluid Group:	Gas or Liquid
PED Fluid State:	Group 2, CAT 2 Gas & Dust
ATEX Regulation:	Fluid GR IIC, Zone 1 & 21
Design Pressure:	-1 to 10 bar at 150°C
Certification:	Supplied as standard with IOMI and vessel inspection certificate

Dimensions







Height Dimensions			
BSP Closure S (2)	L=198	R=41	
BSP Closure S, (3)	L=198	R=41	
Clamp Closure S (2)	L=198	R=41	
Clamp Closure S (3)	L=216	R=59	



** Closure system C and B for PED Group 2, H for PED Group 1 Vent and drain plugs/blanks not supplied as standard, available as separate parts.

Parker has a continuous policy of product development and although the company reserves the right to change specifications, it attempts to keep customers informed of any alterations. This publication is for general information only and customers are requested to contact our sales department for detailed information and advice on a products suitability for specific applications. All products are sold subject to the company's standard of sale.